

iBA KiMYA SAN. ve TiC. A.Ş.
1. Organize Sanayi Bölgesi
Oğuz Caddesi No:22
06930 Sincan / Ankara / Türkiye
Tel:+90312 267 09 83 Fax:+90312 267 09 87
www.iba.com.tr

TEX-ADD

Ürün Teknik Bilgisi

Description

TEX-ADD is an additive which is post added to powder coatings to impart wrinkle effect.

Characteristics

Added by blending into finished product Provide uniform wrinkle effect

Product Properties

Appearance White powder **Specific gravity** 1.2 gr/cm³ **Melting point** 80 – 115°C

Shelf Life 24 months (between 10°C to 40°C in the unopened package)

Application Data

TEX-ADD will provide wrinkle effect when added at levels approximate amount 1.0 - 2.0 % by weight of finished product.

Precautions and Limitations

As a result of possible mixing variations, type and colour of powder coating and stoving conditions, the wrinkle effect may show variation. Applicator may change the addition level of **TEX-ADD** by trial and error to get the desired wrinkle effect.

For uniform wrinkle effect ensure homogenous mixer is obtained.

TEX-ADD should be stored in separate place to prevent cross contamination with other powder coatings.

Transport and Storage

Shipment Not dangerous goods. No special transport requirements.

Storage Conditions Storage temperatures should be kept between 10°C to 40°C in the unopened package.

DISCLAIMER: All the information given in this Data Sheet is the result of our research work experience. It is given in good faith and with every belief in its accuracy but cannot be considered as a formal warranty. In accordance with İBA KİMYA, policy of product development, this specification is subject to change without notice.