

IBAFLEX

Technical Data Sheet

Description

IBAFLEX (...E) powder coating are developed for profiles that need to be bent after painting. **IBAFLEX** powder coatings are available in all chemistry like epoxy, epoxy polyester, polyester and polyurethane.

Characteristics

Excellent flexibility
Bending after painting
Available for all series
Very good mechanical properties
Less waste and pollution to the environment

Applications

White goods
Domestic appliances
Architectural applications

Product Properties

UV Resistance	Check for TDS for the specific series.
Colour	All colours
Surface	Gloss GLE – Semigloss HRE – Semimatt CSE – Matt CME – Wrinkle WRE – Structure STE - SPE
Specific gravity	Check for TDS for the specific series.
Shelf Life	Check for TDS for the specific series.

Application Data

Application	Check for TDS for the specific series.
Curing	Check for TDS for the specific series.
Film Thickness	Check for TDS for the specific series.

Coating Properties

Check TDS for the specific series.

Application Guide

IBAFLEX powder coating does not require a special application. Check TDS for the specific series.

IBAFLEX

Care and Maintenance

IBAFLEX powder coatings should be regularly washed with warm water and mild liquid detergent, followed by a fresh water rinse to maintain the attractive appearance of the powder cured film.

The use of abrasive cleaners is not recommended, nor is the use of active organic solvents.

Health and Safety

The SDS is an integral part of using this product as it contains information on the potential health effect of exposure, personal protective equipment needed. It is recommended to contact to Sales and Customer Service Offices for further information.

Precautions and Limitations

As a result of possible wide application variations and stoving conditions, **IBAFLEX** powder coatings may show variation, between İBA Kimya Powder Coatings prepared samples and production applied material. Therefore, it is the applicator and/or their customer's responsibility to ensure the product conforms to their requirements.

For optimum performance ensures recommended dry film thickness is obtained.

Transport and Storage

Packaging	15-20-25 kgs. Heavy polyethylene bag in a corrugated carton
Shipment	Not dangerous goods. No special transport requirements.
Storage Conditions	Storage temperatures should be kept below 30°C and 50% relative humidity. Powder should be stored in closed containers.

DISCLAIMER: All the information given in this Data Sheet is the result of our research work experience. It is given in good faith and with every belief in its accuracy but cannot be considered as a formal warranty. In accordance with İBA KİMYA, policy of product development, this specification is subject to change without notice.